

MP-PD220

Customer Display



USB



android



Windows



Plug&Play

SPESIFIKASI

Metode Display	: Vacum Fluorescent Display, Green	Compatibility Driver	: OPOS/JPOS Standart
Jumlah Huruf	: 40 (20 kolom x 2 baris)	Commands Mode	: LD220, EPSON POS D101, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL
Kesetaraan	: Epson ESC/POS Command	Language Support	: France, Germany, UK, Denmark, Sweden, Italy, Spain, Japan, Norway, Slavonic, Rusia, Portuguese, Canadian, Nordic, Turkish, Greek
Brightness	: 500~1000 cd/m2	Interface	: RS-232(serial) / USB
Character font	: 5 x 7 dot matrix	Connection Baud rate	: Direct connection 9600 or 19,200 bps
Character type	: 95 Alphanumeric, 32 International Characters	Reliability MTBF	: 30,000 hours
Character size	: 9.02(H) x 5.25(W) mm	Power Consumption	: 5~24 VDC
Dot Size (X x Y)	: 0.86 x 1.05mm	Safety EMC standards	: FCC, CE
Download characters	: 9 characters	OS Pendukung	: Win2000, XP, Vista, Win 7/8/10, Android
Panel Dimension	: 200(W) x 77.5(D) x31(H)mm		
Pole Dimension	: Per support length: 140(L) x 34.5(Dia)mm		
Base Dimension	: 169.5(W) x98.5(D) x39(H)mm		
Viewing Angle	: Max. 90°		
Horizontal Rotation	: Max. 355°		
Weight Approx.	: 980 grams		

KEMASAN

